



N-Uface 602



Face



Finger



RFID



Battery
(Optional)



WiFi



GPRS
(Optional)



Access
Control

Multi-Bio Attendance and Access Control System

Storage Capacity

Face Capacity	3000
Finger Capacity	10,000
Card Capacity	3000
Log Capacity	2,00,000
Max User	3000

Features

- World-class Face Identification Technology
- High-Speed and Accurate Fingerprint Identification
- Face, Fingerprint, Card, Password authentication
- 2 output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Not necessary of bright lights during scans.

supremely low Electric energy consumption.

Comprehensive SDK is available for development & integration.



N-Uface 602

"Molded by our experts we bring you an authentic looking face capture device. N-Uface 602 the most accepted model in industries of the last decade."

N-Uface 602

Communication Interface

Communication	WIFI, TCP/IP, RS232/485, USB
---------------	------------------------------

Biometric

Push Data	YES
4G GPRS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	1 GHz High Speed CPU
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)

Audio/Visual

LCD	4.3" touch screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand in & out	YES
Relay	YES
Support Exit Reader	N-FR12, Wiegand Reader, Remote, Push Button, No Touch

Power & Enviroment

Battery	Optional
Operating Temperature	0°C ~ 50°C
Power	12V DC / 2A
Dimension	192 x 146 x 95 mm



Auto Focus



Low Light Verification



Long Distance Verification



Accepts Color Finger

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.