



SPEEDFACE - 4 SE



Face



RFID



WiFi



USB



Access Control



Live Body Detection



Touch Screen

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	1000
Card Capacity	1000
Max Users	1000
Log Capacity	50,000



Features

Speedy recognition to avoid long queues

Access control to secure your premises

Supremely low electric energy consumption

Auto ON/OFF Eneargy saving light

Dual camera for live body sensing & observation

With and without face mask detection and identification options

2.8 inch touch screen display with easy handling features

SpeedFace - 4 SE

Communication Interface

Communication	WiFi
---------------	------

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.001%
Accuracy ratio	99.27%
Processor	CPUe1.5GHz
OS	Linux
Verification time	<=1 second
Mifare card	Yes



Auto Focus



Autofill light



Long Distance Verification

Audio/Visual

LCD	2.8" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Software Web & Cloud

Access control

Relay	YES
Storage	256MB ROM, 4GB ROM



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Operating Temperature	0°c ~ 60°c
Working Humidity	10% ~ 90%
Power	5V DC / 2A
Dimension	120 x 100 x 27 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.





